

# Specifications

## Tek-Wall Scatter

### 399390

**maharam**

#### Application

Upholstered Walls, Walls

#### Characteristics

Content: 56% Solution-Dyed Polyolefin, 44% Solution-Dyed Post-Consumer Recycled Polyester

Finish: PFOA-Free Stain Resistant

Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 50 yards (46 m)

Weight: 11 oz/ly (339 gr/lm)

Maintenance: W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note: Variations in color and texture are inherent to this textile. This textile can also be produced unbacked.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

#### Price

\$23.00 / C\$34.75 (FOB destination) / C\$31.25 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 50 yards.

#### Performance

Acoustic Rating: Upholstered Walls: ASTM C423 0.65 NRC

Flammability: This textile meets all appropriate flammability requirements for upholstered walls and walls. See flame certificate for test results.

Lightfastness: 200+ Hours



#### Environmental

Greenguard and Greenguard Gold Certified

Contains Recycled Content

FR Free

PFOA-Free Finish

Solution-Dyed Product

Produced in an ISO 14001 Facility

#### Warranty

10 years: Walls

3 years: Upholstered Walls.

© 2008 Maharam

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943