

# Specifications

Kicksilver

399444

**maharam**

## Application

Walls

## Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 23' 4" (305cm x 711cm)

Customs: Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

## Price

Installation is sized, priced and produced on a project-specific basis

## Maintenance

W-Clean with water-based cleanser.



## Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



## Specifications

Kicksilver

399444

**maharam**

### **Environmental**

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

### **Brief**

A composite photograph of a model's stiletto-adorned feet splashing in a puddle of silver-tinted vodka, Kicksilver explores the pathology of glamour.


### **Warranty**

3 years.

© 2009 Marilyn Minter, Maharam under license

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



001