

# Specifications

Process 18

399481

**maharam**

## Application

Walls

## Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 16' 8" (305cm x 508cm)

Customs: Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

## Price

Installation is sized, priced and produced on a project-specific basis

## Maintenance

W-Clean with water-based cleanser.



## Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Process 18  
399481

**maharam**

**Environmental**

Greenguard Gold Certified  
LBC Red List Free  
Contains Bio-Based Content  
FR Free  
Free of Intentionally Added PFAS

**Brief**


Process 18 is part of a series in which Casey Reas assigns behaviors to visual elements without directly controlling them through simple coding that yields complex results. Structure emerges as the behaviors unfold and the elements modify themselves in relation to their environment.

**Warranty**

3 years.

© 2010 Casey Reas, Maharam under license

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943



001