Specifications maharam Pusteblumen

Application

399500

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 16' 8" (305cm x 508cm)

Customs: Scalable Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at

maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours

* "

Specifications
Pusteblumen
399500

maharam

Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief

Using an austere vocabulary of line and wash rendered in the most basic materials - ink, crayon, or gouache on white paper - Silvia Bachli focuses on the space created within and around a drawing, believing that "good drawings are larger than the format decreed by the edge of the paper." While capturing only the most essential aspects of dried dandelions, Bachli retains their wavering, fragile beauty in Pusteblumen.

Warranty

3 years.

© 2010 Silvia Baechli, Maharam under license

Complete product information at maharam.com 800.645.3943



001