Specifications
New World

## **Application**

399510

Walls

### Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 15' (305cm x 457cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

## Price

Installation is sized, priced and produced on a project-specific basis

## Maintenance

W-Clean with water-based cleanser.

# **Testing**

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
New World
399510

## **Environmental**

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

### **Brief**

In New World, hunting decoys and motion-activated toy birds are nestled among a flourishing vine of hybrid Audubon illustrations, providing a tongue-in-cheek commentary on how technological interventions have diluted mankind's experience of nature.

# Warranty

3 years.

© 2010 Francesco Simeti, Maharam under license

Complete product information at maharam.com 800.645.3943



maharam