Specifications
Transition

maharam

399530

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 35' 6" (305cm x 1082cm)

Customs: Repeatable, Scalable Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

......

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications Transition 399530

maharam

Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief


Kees Goudzwaard created this composition for Maharam Digital Projects by utilizing his unique method of creating arrangements with paper before translating them to oil paintings.

Warranty

3 years.

© 2011 Kees Goudzwaard, Maharam under license

Complete product information at maharam.com 800.645.3943



001 Black and Orange 002 Black and White