

Specifications

Tek-Wall Sum

399592

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 72% Solution-Dyed Polyolefin, 28% Solution-Dyed Post-Consumer Recycled Polyester

Finish: PFOA-Free Stain Resistant

Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 50 yards (46 m)

Weight: 11.9 oz/ly (369 gr/lm)

Maintenance: W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$24.00 / C\$36.00 (FOB destination) / C\$32.50 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 50 yards.

Performance

Acoustic Rating: Upholstered Walls: ASTM C423 0.55 NRC

Flammability: This textile meets all appropriate flammability requirements for upholstered walls and walls. See flame certificate for test results.

Lightfastness: 200+ Hours



Environmental

Greenguard and Greenguard Gold Certified

Contains Recycled Content

FR Free

PFOA-Free Finish

Solution-Dyed Product

Produced in an ISO 14001 Facility

Warranty

10 years: Walls

3 years: Upholstered Walls.

© 2013 Maharam

Complete product information at maharam.com

800.645.3943

Specifications

Tek-Wall Sum

399592

maharam



001 Escape




002 Orbit



003 Blizzard



004 Squall



008 Storm