

Specifications

Tek-Wall 1002

399594

maharam

Application

Upholstered Walls, Walls

Characteristics

Content: 51% Solution-Dyed Polyolefin, 49% Solution-Dyed Polyester

Finish: PFOA-Free Stain Resistant

Backing: Acrylic

Width: 54" (137cm)

Bolt Size: 50 yards (46 m)

Weight: 18.8 oz/ly (584 gr/lm)

Maintenance: W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$22.50 / C\$31.75 (FOB destination) / C\$28.25 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 50 yards.

Performance

Acoustic Rating: Upholstered Walls: ASTM C423 0.80 NRC

Flammability: This textile meets all appropriate flammability requirements for upholstered walls and walls. See flame certificate for test results.

Lightfastness: 200+ Hours



Environmental

Greenguard and Greenguard Gold Certified

Contains A Non-Halogenated/Non-Brominated Flame Retardant

PFOA-Free Finish

Solution-Dyed Product

Produced in an ISO 14001 Facility

Warranty

10 years: Walls

3 years: Upholstered Walls.

© 2013 Maharam

Complete product information at maharam.com

800.645.3943

Specifications

Tek-Wall 1002

399594

maharam



001 Simple



002 Shell



003 Tube



004 Tote



005 Foxtrot



006 Trunk



007 Sediment



008 Sound




009 Limbo



010 Canister



011 Vase



012 Cabinet



013 Heritage




014 Mode



015 Drum



016 Ceramic



018 Basin