

Specifications

Cue

399634

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl
Finish: PFAS-Free Protective Topcoat
Backing: Polyester / Cotton Osnaburg
Width: 54" (137cm)
Repeat: Non-match
Bolt Size: 30 yards (27 m)
Class: Type II
Weight: 20 oz/ly (620 gr/lm)
Traffic: High-Suitable for all applications including heavy duty.
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.00 / C\$46.50 (FOB destination) / C\$43.00 (FOB origin)
A \$3.00/C\$4.00 per yard cutting charge applies to orders under 30 yards.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

Testing

Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
BS 476 Adhered*
CAN ULC S102 Adhered
EN 13501 Adhered*
GB 8624 Adhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

☀️ 🔥 🖨️

Specifications

Cue

399634

maharam

Environmental

FR Free

Free of Intentionally Added PFAS

Non-Phthalate Vinyl

Warranty

10 years.

© 2014 Maharam

Complete product information at maharam.com

800.645.3943




003 Doe



004 Beige



005 Mill




006 Cloud




007 Shoal




008 Dorado



013 Porpoise



014 Atmosphere



016 Arctic



017 Placid