

Specifications

Spate

399950

maharam

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester / Cotton Osnaburg

Width: 54" (137cm)

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (620 gr/lm)

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$22.00 / C\$32.50 (FOB destination) / C\$29.00 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 30 yards.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

Testing

Flammability: AS/NZS 3837 Adhered, Group 2

ASTM E 84 Adhered, CLASS A

BS 476 PART 6 Adhered, Class 0*

CAN ULC S102 Adhered, Flame 15, Smoke 30

EN 13501 Adhered, B-s1, d0*

GB 8624, B1 (B-s1,d0)*

*passes with additional treatment

Lightfastness: AATCC 16E, 200+ hours

☒ ☒ ☒

Specifications

Spate

399950

maharam

Environmental

Greenguard and Greenguard Gold Certified

Non-Phthalate Vinyl

FR Free

Pfas-Free

Warranty

10 years.

© 2016 Maharam

Complete product information at maharam.com

800.645.3943



006 Cane



009 Aquatic



010 Steam



014 Lark



015 Script



016 Wedge



018 Rebel