Specifications
Palampore
399978

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 9' 6" x 15' (290cm x 457cm)

Customs: Repeatable, Scalable Country of Origin: USA

Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.

☑ 🌣 🗵 🛱 🎯

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Palampore
399978

Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief

Palampore originated as a series of twenty-one paintings of tree of life imagery interpreted from Palamporeandmdash; a type of hand-painted, mordant-dyed cloth common in India during the 18th and early 19th centuries that was designed primarily for the European export market. Using watercolor paint on Japanese paper, each panel offers a different interpretation of the symbol in both fantastical detail and loose, gestural motifs.

Warranty

3 years.

© 2017 Elisabeth Kley, Maharam under license

Complete product information at maharam.com 800.645.3943



001

maharam