

Specifications
Chenille Cord
by Lisa Scull
407808

maharam

Application

Seating

Characteristics

Content: 43% Solution-Dyed Post-Industrial Recycled Nylon, 42% Solution-Dyed Nylon, 13% Polyester, 2% Polyolefin

Finish: Stain Repellent

Additional Finishes Available: Antimicrobial Stain Resistant Finish with Impermeable Backing, Crypton

Backing: Acrylic

Width: 54" (137cm)

Repeat: ¼" V (1cm V), Suitable for non-match application

Railroaded Repeat: ¼" H (1cm H), Suitable for non-match application

Bolt Size: 55 yards (50 m)

Weight: 22 oz/ly (682 gr/lm)

Country of Origin: Canada

Note: Shown railroaded.

Price

\$75.00 / C\$102.25 (FOB destination) / C\$98.75 (FOB origin)

Maintenance

W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

☒ △ ☒ ☒ Ⓢ

Testing

Abrasion: ASTM D4157, 100,000 double rubs Wyzenbeek

Flammability: BS 5852 Crib 5*

CAL 117-2013

EN 1021-1*

EN 1021-2*

NFPA 260

*passes with additional treatment

Lightfastness: AATCC 16E, 200+ hours

☐ ☀ 🔥 💧 ☆

Specifications
Chenille Cord
by Lisa Scull
407808

maharam

Environmental


Greenguard and Greenguard Gold Certified
Contains Recycled Content
FR Free

Warranty

5 years.

© 2000 Maharam

Complete product information at maharam.com
800.645.3943



006 Flax