Specifications maharam

Emboss

by Konstantin Grcic

466281

Application

Seating

Characteristics

Content: 100% Polyurethane

Finish: None Backing: Polyester Width: 54" (137cm)

Repeat: 3/4" V, 3/4" H (2cm V, 2cm H), Suitable for non-match application

Bolt Size: 50 yards (46 m) Weight: 14.8 oz/ly (459 gr/lm) Country of Origin: Korea

Price

\$62.00 / C\$82.50 (FOB destination) / C\$79.00 (FOB origin)

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

Testing

Abrasion: ASTM D4157, 70,000 double rubs Wyzenbeek

ASTM D4966, 100,000 cycles Martindale

 $Note: A brasion \ test \ results \ exceeding \ ACT \ Performance \ Guidelines \ are \ not \ an \ indicator \ of \ product \ lifespan.$

Multiple factors affect fabric durability and appearance retention.

Flammability: CAL 117-2013

GB/T 17591*

*passes with additional treatment

Lightfastness: AATCC 16E, 200+ hours



Specifications maharam

Emboss by Konstantin Grcic 466281

Environmental

Greenguard and Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free REACH Compliant FR Free PFAS-Free

Warranty

5 years.

© 2015 Maharam

Complete product information at maharam.com 800.645.3943



008 Cobalt