Specifications maharam Legerdemain

Application

300029

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 16' 8" (305cm x 508cm)

Customs: Repeatable, Scalable Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: ASTM E 84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours

* "

Specifications
Legerdemain
300029

Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief

A digital composition based on sixteen paintings by Matt Connors, Legerdemain combines two types of seemingly disparate marks: structural elements such as clean lines and framing devices with spontaneous applications of dripped, brushed, gestural, saturated, or transparent paint. As though freshly revealed, the forms create the illusion of being simultaneously fluid and fixed, absorbent and permeable, light and solid.

Warranty

3 years.

© 2018 Matt Connors, Maharam under license

Complete product information at maharam.com 800.645.3943



001

maharam