Specifications maharam Cleft

300036

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: Protective Topcoat Backing: Cotton Osnaburg

Width: 52" (132cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 25 oz/ly (775 gr/lm)

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$30.50 / C\$47.25 (FOB destination) / C\$43.75 (FOB origin) A \$3.00/C\$4.00 per yard cutting charge applies to orders under 30 yards.

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered GB 8624 Adhered*

*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours



Specifications Cleft 300036

maharam

Environmental

Greenguard Certified REACH Compliant Free of Intentionally Added PFAS Non-Phthalate Vinyl

Warranty

10 years.

© 2019 Maharam

Complete product information at maharam.com 800.645.3943



025 Wrought