Specifications maharam
Poplar

300041

Application

Walls

Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester / Cotton Osnaburg

Width: 52" (132cm) Repeat: Non-match Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (620 gr/lm)

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$36.50 / C\$53.00 (FOB destination) / C\$49.50 (FOB origin)
A \$3.00/C\$4.00 per yard cutting charge applies to orders under 30 yards.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered BS 476 Adhered* CAN ULC S102 Adhered EN 13501 Adhered* GB 8624 Adhered* *passes with additional treatment

passes will additional fredition

Lightfastness: AATCC 16.3, 200+ hours



Specifications Poplar 300041

maharam

Environmental

Greenguard Certified FR Free Free of Intentionally Added PFAS Non-Phthalate Vinyl

Warranty

10 years.

© 2019 Maharam

Complete product information at maharam.com



031 Flagstone