Specifications maharam Score

300049

Application

Walls

Characteristics

Content: 100% Cellulose

Finish: None

Backing: 84% Polyester, 16% Post-Consumer Recycled Polyester

Width: 52" (132cm)

Repeat: 24" V, 52" H (61cm V, 132cm H)

Bolt Size: 30 yards (27 m) Weight: 8.5 oz/ly (264 gr/lm)

Traffic: Moderate-Suitable for heavy duty applications with the exception of high traffic corridors.

Country of Origin: USA

Note: This product is available in custom colors for a minimum of 30 yards.

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$61.00 / C\$86.00 (FOB destination) / C\$82.50 (FOB origin)
A \$3.00/C\$4.00 per yard cutting charge applies to orders under 30 yards.

Maintenance

W-Clean with water-based cleanser.

Testing

Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered CAN ULC S102 Adhered EN 13501 Adhered* ISO 5660 Adhered *passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



74.24

Specifications maharam Score

Environmental

300049

Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Warranty

3 years.

© 2019 Maharam

Complete product information at maharam.com 800.645.3943



001 Tangent



002 Starstruck



003 Manuka



004 Poblano



005 Varsity



006 Freestyle



007 Sled



008 Delve



009 Queue



010 Pomodoro