Specifications Hellion Equilibrium 300074

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat Backing: None Reference Dimension: 10' x 100' (305cm x 3048cm) Customs: Repeatable, Scalable Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser. $\bowtie \bowtie \bowtie \bowtie \bowtie$

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours ***** # **•**

Specifications Hellion Equilibrium 300074

maharam

Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief

Echoing a permanent site-specific installation that was rendered in glass at a New York subway station, Hellion Equilibrium's evolving spectrum of bold color and jagged geometric forms reference the psychological, economic and physical entanglement created by the global modern world - both human and machine.

Warranty

3 years.

© 2020 Sarah Morris, Maharam under license

Complete product information at maharam.com 800.645.3943

