Specifications
Tek-Wall 1003
300089

maharam

Application
Upholstered Walls, Walls

Characteristics
Content: 62% Solution-Dyed Polyolefin, 38% Polyester
Finish: Stain Repellent
Backing: Acrylic
Width: 56" (142cm)
Bolt Size: 40 yards (37 m)
Weight: 17.5 oz/ly (543 gr/lm)
Traffic: High-Suitable for all applications including heavy duty.
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price
Contact your sales representative for pricing.
A cutting charge applies for orders under 40 yards.

Maintenance
W/S/B-Clean with water-based cleanser; mild, water-free dry cleaning solvent, or diluted household bleach.

Testing
Acoustics: ASTM C423, 0.75 NRC

Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
ASTM E84 Unadhered
CAN ULC S102 Adhered
CAN ULC S102 Unadhered
EN 13501 Adhered*
EN 13501 Unadhered*
GB 8624 Adhered*
GB 8624 Unadhered*
ISO 5660 Adhered
*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

Specifications
Tek-Wall 1003
300089

maharam

Environmental
Greenguard Gold Certified
REACH Compliant
FR Free

Warranty
10 years: Walls
3 years: Upholstered Walls.

© 2022 Maharam

Complete product information at maharam.com
800.645.3943

001 Subtle

002 Snowstorm

003 Clarity

004 Drumbeat

005 Centerpiece

006 Flowerpot

007 Boscage

008 Wildland

009 Bluestem

010 Watercraft

011 Tower

012 Archipelago

013 Lentic

014 Elemental

015 Moonset

016 Legend

017 Percussion

018 Viola


019 Crustacean


020 Amphora

021 Nutshell

022 Verve

023 Mellifluous

024 Snickerdoodle

025 Riddle

10.24