

# Specifications

Flaxen

397130

**maharam**

## Application

Walls

## Characteristics

Content: 100% Non-Phthalate Vinyl

Finish: None

Backing: Polyester / Cotton Osnaburg

Width: 54" (137cm)

Repeat: Non-match

Bolt Size: 30 yards (27 m)

Class: Type II

Weight: 20 oz/ly (620 gr/lm)

Traffic: High-Suitable for all applications including heavy duty.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

## Price

\$24.50 / C\$36.75 (FOB destination) / C\$33.25 (FOB origin)

A \$3.00/C\$4.00 per yard cutting charge applies to orders under 30 yards.

## Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

☒ △ ☒ ☒ Ⓜ

## Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered\*

CAN ULC S102 Adhered

EN 13501 Adhered\*

GB 8624 Adhered\*

ISO 5660 Adhered

\*passes with additional treatment

Lightfastness: AATCC 16.3, 200+ hours

☀️ 🔥 🖨️

Specifications  
Flaxen  
397130

**maharam**

**Environmental**

Greenguard Certified  
FR Free  
Free of Intentionally Added PFAS  
Non-Phthalate Vinyl

**Warranty**

10 years.

© 2002 Maharam

Complete product information at [maharam.com](http://maharam.com)  
800.645.3943



125 Dove