

Specifications

Wood Wall As Safari Vest

399470

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 14' 9.5" (305cm x 451cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Wood Wall As Safari Vest
399470

maharam

Environmental

Greenguard Gold Certified
LBC Red List Free
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Brief


Wood Wall as Safari Vest is a floor-to-ceiling sculpture composed of plywood shingles scavenged from an art crating shop. Manifesting the pervasiveness of consumerism, everyday items tacked to the Wood Wall are reverently transformed into art.

Warranty

3 years.

© 2010 Phoebe Washburn, Maharam under license

Complete product information at maharam.com
800.645.3943



001