

# Specifications

## Wood Wall As Safari Vest

### 399470

**maharam**

#### Application

Walls

#### Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 14' 9.5" (305cm x 451cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](https://maharam.com).

#### Price

Installation is sized, priced and produced on a project-specific basis

#### Maintenance

W-Clean with water-based cleanser.

☒ ☒ ☒ ☒ ☒

#### Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



# Specifications

## Wood Wall As Safari Vest

### 399470

**maharam**

#### **Environmental**

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

#### **Brief**

Wood Wall as Safari Vest is a floor-to-ceiling sculpture composed of plywood shingles scavenged from an art crating shop. Manifesting the pervasiveness of consumerism, everyday items tacked to the Wood Wall are reverently transformed into art.

#### **Warranty**

3 years.

© 2010 Phoebe Washburn, Maharam under license

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



001