

# Specifications

## Slow Exposure Stripe

### 399477

**maharam**

#### Application

Walls

#### Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 16' 8" (305cm x 508cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](https://maharam.com).

#### Price

Installation is sized, priced and produced on a project-specific basis

#### Maintenance

W-Clean with water-based cleanser.

☒ ☒ ☒ ☒ ☒

#### Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



# Specifications

## Slow Exposure Stripe

### 399477

**maharam**

#### **Environmental**

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

#### **Brief**

Slow Exposure Stripe is a photcollage of London's Brick Lane at night. By slowing the camera's shutter speed, the neon signs that light this bustling street are transformed into fantastical brushstrokes.


#### **Warranty**

3 years.

© 2010 Paul Smith, Maharam under license

Complete product information at [maharam.com](http://maharam.com)

800.645.3943



001