

Specifications

Slow Exposure Stripe

399477

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: Protective Topcoat

Backing: None

Reference Dimension: 10' x 16' 8" (305cm x 508cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16E, 40+ hours



Specifications
Slow Exposure Stripe
399477

maharam

Environmental

Greenguard and Greenguard Gold Certified
Contains Bio-Based Materials
PFAS-Free

Brief

Slow Exposure Stripe is a photocollage of London's Brick Lane at night. By slowing the camera's shutter speed, the neon signs that light this bustling street are transformed into fantastical brushstrokes.

Warranty

3 years.

© 2010 Paul Smith, Maharam under license

Complete product information at maharam.com
800.645.3943



001