Specifications maharam Wavelength

# **Application**

399478

Walls

### Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 14' 1" (305cm x 429cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

# Price

Installation is sized, priced and produced on a project-specific basis

# Maintenance

W-Clean with water-based cleanser.

# **Testing**

Flammability: AS/NZS 3837 Adhered ASTM E 84 Adhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Wavelength
399478

# maharam

## **Environmental**

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

### **Brief**

In her silver gelatin ocean portraits, photographer Joni Sternbach uses the familiarity of her subject matter as a blank screen for contemplation. Wavelength explores the elasticity of time, whether in permanent suspension or extending eternally.

# Warranty

3 years.

© 2010 Joni Sternbach, Maharam under license

Complete product information at maharam.com 800.645.3943



001