

Specifications

Taurus

399484

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 77' 6" (305cm x 2362cm)

Customs: Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

BS 476 Adhered*

CAN ULC S102 Adhered

ISO 5660 Adhered

*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Taurus

399484

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

Sarah Morris's work often employs vividly colored shapes in a grid-and-tile structure. Taurus, which was originally executed in household gloss, suggests dimensionality while remaining super flat.

Warranty

3 years.

© 2010 Sarah Morris, Maharam under license

Complete product information at maharam.com

800.645.3943



001