

Specifications
Ikebana
399485

maharam

Application
Walls

Characteristics

Content: 65% Cellulose, 35% Latex
Finish: PFAS-Free Protective Topcoat
Backing: None
Reference Dimension: 10' x 16' 8" (305cm x 508cm)
Customs: Scalable
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
CAN ULC S102 Adhered
ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Ikebana

399485

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

Combining ancient analog processes with modern technology, Ikebana was originally conceived as a kinetic sculpture. By placing vivid transparencies of traditional ikebana flower arrangement on a mechanized light table, images continuously overlap, rendering the ikebana mutable.

Warranty

3 years.

© 2010 Jon Kessler, Maharam under license

Complete product information at maharam.com

800.645.3943



001