

Specifications
Silent Rhythm
399539

maharam

Application
Walls

Characteristics

Content: 65% Cellulose, 35% Latex
Finish: PFAS-Free Protective Topcoat
Backing: None
Reference Dimension: 10' x 20' (305cm x 610cm)
Customs: Scalable
Country of Origin: USA
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.
Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered
ASTM E 84 Adhered
CAN ULC S102 Adhered
ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications
Silent Rhythm
399539

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

Using black monofilament, Jacob Hashimoto arranges kites in a floating tapestry, forming a complex matrix that is at once dense and ethereal. Silent Rhythm is a seamless digital assemblage of sixty-four photographs documenting an installation by Hashimoto for Maharam Digital Projects.

Warranty

3 years.

© 2011 Jacob Hashimoto, Maharam under license

Complete product information at maharam.com

800.645.3943



001