

Specifications

Vinex Atlas / P091

399582

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 10' (305cm x 305cm)

Customs: Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.

☒ ☒ ☒ ☒ ☒

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

The acronym "Vinex" refers to a supplement of the Dutch government's Fourth Report on Spatial Planning, which was published in the early 1990s and determined the policy direction for housing development in the Netherlands. The definitive reference work on the fifty-two Vinex districts, Vinex Atlas, designed by Studio Joost Grootens, is based on aerial views, plans, site data, and recent on-site photographs. Page 91 documents two districts in Apeldoorn, currently the Netherlands' twelfth-largest city.

Warranty

3 years.

© 2012 Joost Grootens, Maharam under license

Complete product information at maharam.com

800.645.3943



001