Specifications Screen (Double Desert Inverted) 399585

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex Finish: PFAS-Free Protective Topcoat Backing: None Reference Dimension: 10' x 15' (305cm x 457cm) Customs: Repeatable Country of Origin: USA Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser. $\bowtie \bowtie \bowtie \bowtie \bowtie$

Testing

Flammability: AS/NZS 3837 Adhered ASTM E84 Adhered ASTM E84 Unadhered CAN ULC S102 Adhered ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours * # #

Specifications Screen (Double Desert Inverted) 399585

Environmental

Greenguard Gold Certified LBC Red List Free Contains Bio-Based Content FR Free Free of Intentionally Added PFAS

Brief

For Screen (Double Desert Inverted), Kevin Appel enlarged a found image until its granular CMYK rosettes were revealed. Flipped and repeated, the image then received layers of "interference" in the form of details extracted from one of Appel's photographs of the Salton Sea and rhythmic white triangles. Seen through this screen of architectonic abstraction, the final composition offers a view of nature that is at once recognizable and disorienting.

Warranty

3 years.

© 2012 Kevin Appel, Maharam under license

Complete product information at maharam.com 800.645.3943

