

Specifications
Metropolis
399647

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: Protective Topcoat

Backing: None

Reference Dimension: 10' x 15' (305cm x 457cm)

Customs: Repeatable, Scalable

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16E, 40+ hours



Specifications
Metropolis
399647

maharam

Environmental

Greenguard and Greenguard Gold Certified
LBC Red List Free
Contains Bio-Based Materials
PFAS-Free

Brief

Through a complex maze of commuters, trains, cars, and infrastructure, Metropolis captures the bustling nature of the urban environment. Upon closer inspection, interactions between people and anthropomorphic buildings emerge.

Warranty

3 years.

© 2014 Andy Rementer, Maharam under license

Complete product information at maharam.com
800.645.3943



001