

Specifications

Ume

by Toyo Ito

399741

maharam

Application

Walls

Characteristics

Content: 83% Cellulose, 17% Polyester

Finish: PFAS-Free Protective Topcoat

Backing: None

Width: 27" (69cm)

Repeat: 27" V, 27" H (69cm V, 69cm H)

Weight: 4.8 oz/ly (149 gr/lm)

Traffic: Moderate-Suitable for heavy duty applications with the exception of high traffic corridors.

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$203.50 / C\$278.50 (FOB destination) / C\$275.00 (FOB origin)

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Ume

by Toyo Ito

399741

maharam

Environmental

Greenguard Gold Certified

Healthier Hospitals Compliant

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

For Ume, Toyo Ito looked to the natural yet complex branching system of the Japanese plum tree. The intertwining branches form a canopy under a clear blue sky.


Warranty

3 years.

© 2015 Toyo Ito, Maharam under license

Complete product information at maharam.com

800.645.3943



001