Specifications
Tenor

maharam

399832

Application

Walls

Characteristics

Content: 92% Rayon, 8% Nylon Finish: PFAS-Free Water Repellent Backing: Cellulose / Polyester

Width: 54" (137cm) Repeat: Non-match Bolt Size: 55 yards (50 m) Weight: 12.5 oz/ly (388 gr/lm)

Traffic: Low-Suitable for private offices, conference rooms, residential and low traffic applications where

superior cleanability is not a priority. Not appropriate for corridor applications.

Country of Origin: Netherlands

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

\$121.00 / Not available in Canada

A \$3.00 per yard cutting charge applies to orders under 55 yards.

Maintenance

X-Vacuum or brush lightly to remove surface dust.

図 ☆ 図 ⊠ 図 図

Testing

Flammability: ASTM E84 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications maharam
Tenor

Environmental

399832

Greenguard Gold Certified REACH Compliant Contains Forest Stewardship Council (Fsc) Certified Content FR Free

Warranty

1 year.

© 2016 Maharam

Complete product information at maharam.com 800.645.3943

