

Specifications

Nuage

399952

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 13' 4" (305cm x 406cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at

maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.



Testing

Flammability: AS/NZS 3837 Adhered

ASTM E 84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours



Specifications

Nuage

399952

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

FR Free

Free of Intentionally Added PFAS

Brief

Translated from a watercolor, metallic paint, and pencil study of a cloudy sky, Nuage is based on an early Journal Drawing from a series of weekly drawings dating from 2003. By preserving the intermediary stages of its creation in blank areas that dissipate with the grid's ascending proportions, Nuage explores how a drawing can document the passage of time.

Warranty

3 years.

© 2016 Henri Jacobs, Maharam under license

Complete product information at maharam.com

800.645.3943



001