

Specifications

Ito

399970

maharam

Application

Walls

Characteristics

Content: 65% Cellulose, 35% Latex

Finish: PFAS-Free Protective Topcoat

Backing: None

Reference Dimension: 10' x 36' 8" (305cm x 1118cm)

Customs: Repeatable, Scalable

Country of Origin: USA

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price

Installation is sized, priced and produced on a project-specific basis

Maintenance

W-Clean with water-based cleanser.

☒ ☒ ☒ ☒ ☒

Testing

Flammability: AS/NZS 3837 Adhered

ASTM E84 Adhered

CAN ULC S102 Adhered

ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours

☀️ 🔥 🖨️

Specifications

Ito

399970

maharam

Environmental

Greenguard Gold Certified

LBC Red List Free

Contains Bio-Based Content

FR Free

Free of Intentionally Added PFAS

Brief

Ito is based on a series of photographs taken by Miranda Lichtenstein during a residency in Ito, Japan. Using a 4x5 camera that allowed her to create areas of sharp focus, distortion, and doubling within a single plane, Lichtenstein photographed still-life arrangements against a backdrop of reflective mylar and handmade Japanese Washi paper.


Warranty

3 years.

© 2017 Miranda Lichtenstein, Maharam under license

Complete product information at maharam.com

800.645.3943



001